

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
7 February 2002 (07.02.2002)

PCT

(10) International Publication Number
WO 02/11112 A2

(51) International Patent Classification: G09G

(21) International Application Number: PCT/US01/23892

(22) International Filing Date: 26 July 2001 (26.07.2001)

(23) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/638,122 28 July 2000 (28.07.2000) US
09/916,232 25 July 2001 (25.07.2001) US

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GR, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MY, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TD, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LI, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant: CLAIRVOYANTE LABORATORIES, INC. [US/US]; 120 Pleasant Hill Avenue, N., Sofia 190, Schastopol, CA 94575 (US).

Published:


without international search report and to be republished upon receipt of that report

(72) Inventor: BROWN-ELLIOTT, Candice, Helen; 531 York Street, Vallejo, CA 94590 (US).

(74) Agents: D'ALESSANDRO, Kenneth et al.; Sierra Patent Group, Ltd., P.O. Box 6145, Simsbury, NY 89449 (US).

For more-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: ARRANGEMENT OF COLOR PIXELS FOR FULL COLOR IMAGING DEVICES WITH SIMPLIFIED ADDRESSING



(57) Abstract: An array and row and column line architecture for a display is disclosed. The array consists of a plurality of row and column positions and a plurality of three-color pixel elements. A three-color pixel element can comprise a blue emitter, a pair of red emitters, and a pair of green emitters. Several designs for the three-color pixel element are contemplated. The drive matrix consists of a plurality of row and column drivers to drive the individual emitters. The row drivers drive the red, green and blue emitters in each row. The red and green emitters in each column are driven by a single column driver. However, a single column driver can drive two column lines of blue emitters, a first column line and a second column line of the next nearest neighboring three-color pixel element. Methods of driving a three-color pixel element are also disclosed.

WO 02/11112 A2

WO 02/11112

PCT/US01/23892

5

SPECIFICATIONARRANGEMENT OF COLOR PIXELS FOR FULL COLOR IMAGING DEVICES WITH
SIMPLIFIED ADDRESSING

10

BACKGROUND

The present application relates to color pixel arrangements, and specifically to color pixel arrangements used in electronic imaging devices and displays.

Full color perception is produced in the eye by three-color receptor nerve cell types called cones. The three types are sensitive to different wavelengths of light: long, medium, and short ("red", "green", and "blue", respectively). The relative density of the three differs significantly from one another. There are slightly more red receptors than green receptors. There are very few blue receptors compared to red or green receptors. In addition to the color receptors, there are relative wavelength insensitive receptors called rods that contribute to monochrome night vision.

20

The human vision system processes the information detected by the eye in several perceptual channels: luminance, chrominance, and motion. Motion is only important for flicker threshold to the imaging system designer. The luminance channel takes the input from all of the available receptors, cones and rods. It is "color blind". It processes the information in such a manner that the contrast of edges is enhanced. The chrominance channel does not have edge contrast enhancement. Since the luminance channel uses and enhances every receptor, the resolution of the luminance channel is several times higher than the chrominance channel. The blue receptor contribution to luminance perception is less than 5%, or one part in twenty. Thus, the error introduced by lowering the blue resolution by one octave will be barely noticeable by the most perceptive viewer, if at all, as experiments at NASA, Ames Research Center (R. Martin, J. Gille, J. Larimer, Detectability of Reduced Blue Pixel Count in Projection Displays, STD Digest 1993) have demonstrated.

25

30

Color perception is influenced by a process called "assimilation", or the Von Bezold color blending effect. This is what allows separate color pixels (or sub-pixels or emitters) of a display to be perceived as the mixed color. This blending effect happens over a given angular distance in the field of view. Because of the relatively scarce blue receptors, this blending happens over a greater angle for blue than for red or green. This distance is approximately 0.25° for blue, while for red or green it is approximately 0.12° . At a viewing

35

WO 02/11112

PCT/US01/23892

5 distance of twelve inches, 0.25° subtends 50 mils ($1,270 \mu$) on a display. Thus, if the blue pixel pitch is less than half (625μ) of this blending pitch, the colors will blend without loss of picture quality.

The present state of the art of color single plane imaging matrix, for flat panel displays and solid state camera chips is the (red green-blue) RGB color triad. The system
10 takes advantage of the Von Bezold effect by separating the three colors and placing equal spatial frequency weight on each color. Two manufacturers have shown improvements in display design by using dual or triple panels whose images are superimposed. One manufacturer of projection displays used three panels, red, green, and blue. The blue panel utilizes reduced resolution in accordance with the match between human vision requirements
15 and the displayed image. Another manufacturer, Planar Systems of Beaverton, Oregon employs a "Multi-row Addressing" technique having a dual electroluminescent panel, one panel with red and green pixels, the other with blue pixels to build a developmental model. The blue pixels have reduced resolution in the vertical axis only. This allows the blue phosphors to be excited at a higher rate than the red and green pixels, thus overcoming a
20 problem with lower blue phosphor brightness. The problem with the prior art is that in providing the same matched resolution balance between human vision and display, additional display panels/planes are used, along with additional driver electronics.

Other display methods such as disclosed in U.S. Patent No. 6,008,868 to Silverbrook use binary controlled emitters. In using binary controlled emitters, each emitter has a discrete
25 luminance value, therefore, requiring the display to have an exact area to luminance relationship. This prior art used reduced blue "bit depth" built into the panel in accordance with human vision's lower blue color space increments. Conventional display methods also use a single color in a vertical stripe. Since conventional stripes have limited the Modulation Transfer Function (MTF), high spatial frequency resolution, in the horizontal axis, stripes of
30 a single color are non-optimal.

Display devices can include liquid crystal display (LCD) devices. LCD devices have been used in a variety of applications, including calculators, watches, color televisions, and computer monitors. A conventional liquid crystal panel typically includes a pair of transparent glass substrates that are arranged in parallel to define a narrow gap therebetween
35 that is filled with a liquid crystal material. A plurality of pixel electrodes typically are disposed in a matrix on an inner surface of one of the transparent glass substrates, and a plurality of common electrodes corresponding to the pixel electrodes are arranged on the

WO 02/11112

PCT/US01/23892

5 inner surface of the other substrate of the two transparent glass substrates. A liquid crystal cell is defined by opposing pixel electrodes and common electrodes. Images are displayed by controlling light transmission through the cell according to a voltage applied to the electrode pair.

10 In a conventional active matrix LCD device, a plurality of row lines are formed on one substrate, transverse to a plurality of column lines. A plurality of pixel electrodes are disposed on a corresponding plurality of pixels regions defined by the row and column lines. A respective thin-film transistor (TFT) is formed on a respective one of the pixel regions, and drives the pixel electrode formed thereon.

15 Repeatedly driving a liquid crystal cell with voltages having the same polarity can cause an electrochemical change in the pixel electrode and the common electrode due to migration of ionic impurities within the liquid crystal material. This change can significantly reduce display sensitivity and brightness. Accordingly, it is generally desirable to repeatedly invert the polarity of the voltage applied to the liquid crystal cell in order to prevent this phenomenon. This method of driving a liquid crystal cell is known as "inversion". There are several inversion schemes that are known in the art, including "frame inversion", "column inversion", "line (or row) inversion", or "dot inversion".

20 A conventional dot inversion driving technique involves applying column line voltages that have different polarities to adjacent sub-pixel electrodes, for example, by driving alternating pixel elements with negative and positive voltages. Typically, the polarity of the driving voltage applied to a given pixel electrode is inverted each time the voltage is applied. The applied voltage is stored on the sub-pixel, row by row, alternating with each row. The result is a "checker board" pattern of polarities on the two dimensional matrix of sub-pixels.

25 Although the above mentioned conventional dot-inversion driving technique is useful to prevent ion migration in the liquid crystal material and lowering perceived "flicker" in the display. Special care must be taken when applying "dot inversion" to the novel arrangement of the three color pixel elements, and its associated drive structure to avoid this "flicker".

SUMMARY

35 The drawbacks and disadvantages of the prior art are overcome by the arrangement of color pixels for full color imaging devices with simplified addressing.

WO 02/11112

PCT/US01/23892

5 An array and row and column line architecture for a display is disclosed. The array consists of a plurality of row and column positions and a plurality of three-color pixel elements. Each three-color pixel element can comprise a blue emitter, a pair of red emitters, and a pair of green emitters. Several designs for the three-color pixel element are contemplated. The drive matrix consists of a plurality of row and column drivers to drive the
10 individual emitters. The row drivers drive the red, green and blue emitters in each row. The red and green emitters in each column are driven by a single column driver. However, a single column driver can drive two column lines of blue emitters, a first column line and a second column line of the next nearest neighboring three-color pixel element. Thus, the number of column lines and associated driver electronics, as used in the prior art, are reduced
15 in the present invention.

 A drive matrix for an array of three-color pixel elements is also disclosed. While the array consists of a plurality of rows and columns of each three-color pixel element of the present invention, the drive matrix consists of a plurality of row and column drivers to drive the individual emitters. The row drivers drive the red, green and blue emitters in each row.
20 The red and green emitters in each column are driven by a single column driver. However, a single column driver can drive two column lines of blue emitters, a first column line and a second column line of the next nearest neighboring three-color pixel element. Thus, also reducing the number of column lines and associated driver electronics.

 Methods of driving a three-color pixel element in a display are disclosed. The method
25 comprises providing a three-color pixel element having any of several contemplated designs. The blue emitter, the red emitters, and the green emitters are driven, such that the blue emitter of the three-color pixel element is coupled to a blue emitter of a next nearest neighboring three-color pixel element.

30 BRIEF DESCRIPTION OF THE DRAWINGS

 Referring now to the figures, wherein like elements are numbered alike:
 FIG. 1 is an arrangement of a three-color pixel element;
 FIG. 2 is another arrangement of a three-color pixel element;
 FIG. 3 is an array of three-color pixel elements;
35 FIG. 4 is an arrangement of two three-color pixel elements, aligned horizontally;
 FIG. 5 is a diagram showing an illustrative drive matrix for the pixel arrangement of FIG. 4;

WO 02/11112

PCI/US01/23892

5 FIG. 6 is an arrangement of four three-color pixel elements, aligned horizontally;
 FIG. 7 is a diagram showing an illustrative drive matrix for the pixel arrangement of
 FIG. 6;

 FIG. 8 is another arrangement of four three-color pixel elements, aligned horizontally;
 FIG. 9 is a diagram showing an illustrative drive matrix for the pixel arrangement of
10 FIG. 8;

 FIG. 10 is another arrangement of four three-color pixel elements, aligned
 horizontally;

 FIG. 11 is a diagram showing an illustrative drive matrix for the pixel arrangement of
 FIG. 10;

15 FIG. 12 is another arrangement of four three-color pixel elements, aligned
 horizontally;

 FIG. 13 is a diagram showing an illustrative drive matrix for the pixel arrangement of
 FIG. 12;

 FIG. 14 is a diagram illustrating a dot inversion scheme for the pixel arrangement of
20 FIG. 6;

 FIG. 15 is another diagram illustrating a dot inversion scheme for the pixel
 arrangement of FIG. 8;

 FIG. 16 is an alternate diagram for FIG. 15 also illustrating a dot inversion scheme for
 the pixel arrangement of FIG. 8;

25 FIG. 17 is another diagram illustrating a dot inversion scheme for the pixel
 arrangement of FIG. 10;

 FIG. 18 is an alternate diagram for FIG. 17 also illustrating a dot inversion scheme for
 the pixel arrangement of FIG. 10;

 FIG. 19 is another diagram illustrating a dot inversion scheme for the pixel
30 arrangement of FIG. 12; and

 FIG. 20 is an alternate diagram for FIG. 19 also illustrating a dot inversion scheme for
 the pixel arrangement of FIG. 10.

DETAILED DESCRIPTION

35 Those of ordinary skill in the art will realize that the following description of the
 present invention is illustrative only and not in any way limiting. Other embodiments of the
 invention will readily suggest themselves to such skilled persons.

WO 02/11112

PCT/US01/23892

5 The arrangement of three-color pixel elements influences the effect of the blending of the colors of the pixels. Each three-color pixel element comprises at least a blue emitter, a red emitter, and a green emitter and can be group in several different designs. A plurality of row drivers and column (or column line) drivers are operated to drive the individual emitters. The row drivers drive the red, green and blue emitters in each row. The red and green
10 emitters in each column are driven by a single column driver. However, reduction of the number of column drivers can be achieved by using a single column driver to drive two column lines of blue emitters, a first column line and a second column line of the next nearest neighboring three-color pixel element. This arrangement aids in the driving of the display device, especially liquid crystal display devices, by dot inversion methods.

15 FIG. 1 shows an illustrative embodiment of an arrangement of a three-color pixel element 10. The three-color pixel element consists of a blue emitter 12, two red emitters 14, and two green emitters 16. The three-color pixel element 10 is square shaped and is centered at the origin of an X, Y coordinate system. The blue emitter 12 is centered at the origin of the square and extends into the first, second, third, and fourth quadrants of the X, Y coordinate
20 system. A pair of red emitters 14 are disposed in opposing quadrants (i.e., the second and the fourth quadrants), and a pair of green emitters 16 are disposed in opposing quadrants (i.e., the first and the third quadrants), occupying the portions of the quadrants not occupied by the blue emitter 12. As shown in FIG. 1, the blue emitter 12 is square shaped, having corners aligned at the X and Y axes of the coordinate system, and the opposing pairs of red 14 and
25 green 16 emitters are generally square shaped, having truncated inwardly-facing corners forming edges parallel to the sides of the blue emitter 12.

 Another illustrative embodiment of a three-color pixel element 20 is shown in FIG. 2. In this embodiment, the three-color pixel element 20 is also square shaped and is centered at the origin of an X, Y coordinate system, extending into the first, second, third, and fourth
30 quadrants of the X, Y coordinate system. The blue emitter 22 is centered at the origin of the square and is square shaped having sides aligned parallel to the X and Y axes of the coordinate system. A pair of red emitters 24 are disposed in opposing quadrants (i.e., the second and the fourth quadrants), and a pair of green emitters 26 are disposed in opposing quadrants (i.e., the first and the third quadrants), occupying the portions of the quadrants not
35 occupied by the blue emitter 22. In this embodiment, the opposing pairs of red emitters 24 and green emitters 26 are L-shaped. The L-shaped emitters envelop the blue emitter having the inside corners of the L-shaped emitters aligned with the corners of the blue emitter.

WO 02/11112

PCT/US01/23892

5 According to a preferred embodiment, the three-color pixel element has equal red, green and blue emitter areas. This may be achieved by placing in the center of the three-color pixel element a blue emitter having an area larger than the areas of the individual red and green emitters. Those of ordinary skill in the art will recognize that, in other embodiments, the area of the blue emitter may be smaller in relation to either the red or green emitters. The blue emitter can be brighter than either the red or green emitters can, or it can be the same
10 brightness as the red and green emitters can. For example, the drive-to-luminance gain of the blue emitter may be greater than that of the red or green emitters.

 Although the above description is illustrative of a preferred embodiment, those of ordinary skill in the art will readily recognize other alternatives. For example, the emitters
15 may have different shapes, such as rounded or polygonal. They may also be diffuse rather than having sharp edges. The three-color pixel elements need not be arranged with equal spatial frequency in each axis. The aperture ratio between the emitters may be minimized to substantially non-existent or it may be very pronounced, and the space may also be different colors, including black or white. The emitters may be any technology known or invented in
20 the future, such as displays using Liquid Crystal (LCD), Plasma, Thin Film Electroluminescent, Discrete Light Emitting Diode (LED), Polymer Light Emitting Diode, Electro-Chromic, Electro-Mechanical, Incandescent Bulb, or Field Emission excited phosphor (FED).

 FIG. 3 is an array 30 of the three-color pixel elements 10 of FIG. 1. The array 30 is
25 repeated across a panel or chip to complete a device with a desired matrix resolution. The repeating three-color pixel elements 10 form a "checker board" of alternating red 32 and green 34 emitters with blue emitters 36 distributed evenly across the device, but at half the resolution of the red 32 and green 34 emitters.

 One advantage of the three-color pixel element array is improved resolution of color
30 displays. This occurs since only the red and green emitters contribute significantly to the perception of high resolution in the luminance channel. Thus, reducing the number of blue emitters and replacing some with red and green emitters improves resolution by more closely matching human vision.

 Dividing the red and green emitters in half in the vertical axis to increase spatial
35 addressability is an improvement over the conventional vertical single color stripe of the prior art. An alternating "checkerboard" of red and green emitters allows the Modulation Transfer

WO 02/11117

PCT/US01/23892

- 5 Function (MTF), high spatial frequency resolution, to increase in both the horizontal and the vertical axes.

 The three-color pixel element array may also be used in solid state image capture devices found in modern consumer video cameras and electronic still cameras. An advantage of using the reduced blue emitter resolution in both image capture and display is that stored
10 images do not need to supply the same resolution for each color in storage or processing. This presents potential savings during coding, compression, and decompression of electronically stored images, including software and hardware in electronic imaging and display systems such as computers, video games, and television, including High Definition Television (HDTV) recording, playback, broadcasting, and display.

15 FIG. 4 is an arrangement 40 of two three-color pixel elements aligned horizontally. The three-color pixel elements are square-shaped and each is centered at each origin of an X, Y coordinate system. The blue emitter 42a is centered at the origin of the square of the first three-color pixel element and extends into the first, second, third, and fourth quadrants of its X, Y coordinate system. Blue emitter 42b is centered at the origin of the square of the second
20 three-color pixel element and extends into the first, second, third, and fourth quadrants of its X, Y coordinate system. Red emitters 44a and 44b are disposed in the second quadrants of the first and second pixel elements, respectively. Green emitters 46a and 46b are disposed in the third quadrants of the first pixel and second pixel elements, respectively. Green emitters 48a and 48b are disposed in the first quadrant of the first pixel and second pixel elements.
25 Red emitters 50a and 50b are disposed in the fourth quadrants of the first pixel and second pixel elements, respectively. As shown in FIG. 4, each blue emitter (e.g., 42a) is square-shaped having corners aligned at the X and Y axes of each coordinate system. The opposing pairs of red emitters (e.g., 44a and 50a) and green emitters (e.g., 48a and 46a) are generally square shaped, having truncated inwardly-facing corners forming edges parallel to the sides
30 of the blue emitter (e.g., 42a). In each three-color pixel element, the red and green emitters occupy the portion of the quadrant not occupied by the blue emitter.

 FIG. 5 is a diagram of an illustrative drive matrix 60 for the three-color pixel element arrangement 40. The liquid crystal display emitters are schematically represented as capacitors for convenience. Each liquid crystal display emitter is coupled to the row and
35 column lines through a select transistor, as in FIG. 5 with red emitter 44a. The liquid crystal display emitters are coupled through the gate of the select transistor to the row line. The column line is coupled to the first source/drain terminal of the select transistor and the second

5 source/drain terminal of the select transistor, which is coupled to the liquid crystal display emitter. A fixed potential is coupled to the liquid crystal display emitter. The liquid crystal display emitters of the invention may be active electronic devices such as Thin Film Transistors (TFT) found in Active Matrix Liquid Crystal Display (AMLCD), or Charge Coupled Devices (CCD) as found in camera chips, or other suitable devices.

10 The illustrative drive matrix 60 shown in FIG. 5 consists of a 2 X 5 drive matrix, where four column drivers drive the red and green emitters and a single column driver drives the blue emitters. A first column driver 62 drives the red emitter 44a and the green emitter 46a. The blue emitters 42a and 42b are tied together and driven by a second column driver 64. A third column driver 66 drives the green emitter 48a and the red emitter 50a, while a
15 fourth column driver 68 drives the red emitter 44b and the green emitter 46b. The green emitter 48b and the red emitter 50b are driven by a fifth column driver 70. Alternative embodiments, using at least four three-color pixel elements with two row drivers and ten column drivers, are presented further herein.

The row drivers drive the red, green and blue emitters in each row. Row driver 72
20 drives red emitters 44a and 44b, green emitters 48a and 48b, as well as blue emitter 42b. Row driver 74 drives green emitters 46a and 46b, red emitters 50a and 50b and blue emitter 42a. Each emitter can be driven at continuous luminance values at specific locations in a pixel element, unlike emitters in the prior art, which are driven at discrete luminance values at random locations in a pixel element.

25 The drive matrix uses approximately 16% fewer column drivers to present a given image than does a prior art 2 X 6-drive matrix for the triad arrangement. The column lines are reduced since the blue emitters 12 are combined. This entire arrangement can be turned 90 degrees such that the combined blue emitters 12 are driven by the same row driver. All such topologically identical variants known in the art are possible embodiments. In addition, the
30 driver type, voltage, and timing can be the same as already known in the art for each device technology.

An alternative embodiment of an arrangement and drive matrix is illustrated in FIGS. 6 and 7. FIG. 6 is an arrangement 76 of four three-color pixel elements aligned horizontally. Each three-color pixel element is square-shaped and each is centered at each origin of an X,
35 Y coordinate system. In this case, the blue emitters 80a, 80b, 80c, and 80d are centered at the origin of the square of each of the three-color pixel elements. The blue emitters 80a, 80b, 80c, and 80d extend into the first, second, third, and fourth quadrants of each X, Y coordinate

WO 02/11112

PCT/US01/23892

5 system. Red emitters 52a, 52b, 52c, and 52d are disposed in the second quadrants of the first, second, third, and fourth three-color pixel elements, respectively. Green emitters 54a, 54b, 54c, and 54d are disposed in the third quadrants of the first, second, third, and fourth three-color pixel elements, respectively. Green emitters 56a, 56b, 56c, and 56d are disposed in the first quadrants of the first, second, third, and fourth three-color pixel elements, respectively.

10 Red emitters 58a, 58b, 58c, and 58d are disposed in the fourth quadrants of the first, second, third, and fourth three-color pixel elements, respectively. As shown in FIG. 6, each blue emitter (e.g., 80a) is square-shaped, having corners aligned at the X and Y axes of each coordinate system. The opposing pairs of red emitters (e.g., 52a and 58a) and green emitters (e.g., 54a and 56a) are generally square shaped, having truncated inwardly facing corners forming edges parallel to the sides of the blue emitter (e.g., 80a). In each three-color pixel element, the red and green emitters occupy the portion of the quadrant not occupied by the blue emitter.

15

FIG. 7 is a diagram of an illustrative drive matrix 78 for the arrangement 76. The illustrative drive matrix 78 shown in FIG. 7 consists of a 2 X 10 drive matrix, where eight

20 column drivers drive the eight red and eight green emitters and two column drivers drive the four blue emitters. A first column driver 94 drives the red emitter 52a and the green emitter 54a. The blue emitters 80a and 80c are tied together and driven by a second column driver 96. A third column driver 98 drives the green emitter 56a and the red emitter 58a, while a fourth column driver 100 drives the red emitter 52b and the green emitter 54b. A fifth

25 column driver 102 drives the blue emitter 80b, which is tied together with 80d. The green emitter 56b and the red emitter 58b are driven by a sixth column driver 104, while a seventh column driver 106 drives red emitter 52c and green emitter 54c. An eighth column driver 108 drives green emitter 56c and red emitter 58c, while a ninth column driver 110 drives red emitter 52d and green emitter 54d. Finally, a tenth column driver 112 drives green emitter

30 56d and red emitter 58d.

The row drivers drive the red, green and blue emitters in each pixel row. Row driver 90 drives red emitters 52a, 52b, 52c, and 52d, green emitters 56a, 56b, 56c, and 56d, as well as blue emitters 80c and 80d. Row driver 92 drives green emitters 54a, 54b, 54c, and 54d, red emitters 58a, 58b, 58c, and 58d, and blue emitters 80a and 80b. Each emitter can be

35 driven at continuous luminance values at specific locations in a pixel element, unlike emitters in the prior art, which are driven at discrete luminance values at random locations in a pixel element.

5 The drive matrix uses approximately 16.6% fewer column drivers to present a given image than does a prior art 2 X 12 drive matrix for the triad arrangement. The column lines are reduced since the blue emitters (80a and 80c; 80b and 80d) are combined. The driver type, voltage, and timing can be the same as already known in the art for each device technology.

10 Another embodiment of a three-color pixel element arrangement and drive matrix is illustrated in FIGS. 8 and 9. FIG. 8 is an arrangement 114 of four three-color pixel elements aligned horizontally in an array row. Each three-color pixel element can be square-shaped or rectangular-shaped and has two rows including three unit-area polygons, such that an emitter occupies each unit-area polygon. Disposed in the center of the first pixel row of the first, 15 second, third, and fourth three-color pixel elements are blue emitters 130a, 130b, 130c, and 130d, respectively. Disposed in the center of the second pixel row of the first, second, third, and fourth three-color pixel elements are blue emitters 132a, 132b, 132c, and 132d, respectively. Red emitters 120a, 120b, 120c, and 120d are disposed in the first pixel row, to the left of blue emitters 130a, 130b, 130c, and 130d, of the first, second, third, and fourth 20 three-color pixel elements, respectively. Green emitters 122a, 122b, 122c, and 122d are disposed in the second pixel row, to the left of blue emitters 132a, 132b, 132c, and 132d, of the first, second, third, and fourth three-color pixel elements, respectively. Green emitters 124a, 124b, 124c, and 124d are disposed in the first pixel row, to the right of blue emitters 130a, 130b, 130c, and 130d, of the first, second, third, and fourth three-color pixel elements, respectively. Red emitters 126a, 126b, 126c, and 126d are disposed in the second pixel row, to the right of blue emitters 132a, 132b, 132c, and 132d, of the first, second, third, and fourth 25 three-color pixel elements, respectively.

FIG. 9 is a diagram of an illustrative drive matrix 116 for the three-color pixel element arrangement 114. The illustrative drive matrix 116 shown in FIG. 9 consists of a 2 X 30 16 drive matrix, where eight column drivers drive the eight red and eight green emitters and two column drivers drive the four blue emitters. A first column driver 140 drives the red emitter 120a and the green emitter 122a. The blue emitters 130a, 132a, 130c, and 132c are tied together and driven by a second column driver 142. A third column driver 144 drives the green emitter 124a and the red emitter 126a, while a fourth column driver 146 drives the red emitter 120b and the green emitter 122b. A fifth column driver 148 drives blue emitters 130b 35 and 132b, which are tied together with 130d and 132d. The green emitter 124b and the red emitter 126b are driven by a sixth column driver 150, while a seventh column driver 152

WO 02/11112

PCT/US01/23892

5 drives red emitter 120c and green emitter 122c. An eighth column driver 154 drives green emitter 124c and red emitter 126c, while a ninth column driver 156 drives red emitter 120d and green emitter 122d. Finally, a tenth column driver 158 drives green emitter 124d and red emitter 126d.

The row drivers drive the red, green and blue emitters in each pixel row. Row driver
10 160 drives red emitters 120a, 120b, 120c, and 120d, green emitters 124a, 124b, 124c, and 124d, as well as blue emitters 130a, 132c, 130d, and 132d. Row driver 162 drives green emitters 122a, 122b, 122c, and 122d, red emitters 126a, 126b, 126c, and 126d, and blue emitters 130a, 132a, 130b, and 132b. Each emitter can be driven at continuous luminance values at specific locations in a pixel element, unlike emitters in the prior art, which are
15 driven at discrete luminance values at random locations in a three-color pixel element.

The drive matrix uses approximately 16.6% fewer column drivers to present a given image than does a prior art 2 X 12-drive matrix for the triad arrangement. The column lines are reduced since the blue emitters (130a, 132a and 130c, 132c; 130b, 132b and 130d, 132d) are combined. The driver type, voltage, and timing can be the same as already known in the
20 art for each device technology.

Another embodiment of a three-color pixel element arrangement and drive matrix is illustrated in FIGS. 10 and 11. FIG. 10 is an arrangement 164 of four three-color pixel elements aligned horizontally in an array row. Each three-color pixel element can be square-shaped or rectangular shaped and has two rows with each row including three unit-area
25 polygons, such that an emitter occupies each unit-area polygon. At least one unit-area polygon is at least two times the area of the other unit-area polygons and is occupied by blue emitters 168a, 168b, 168c, and 168d. The blue emitters 168a, 168b, 168c, and 168d can be formed as a single emitter or can be two separate blue emitters wired together.

As illustrated in FIG. 10, blue emitters 168a, 168b, 168c, and 168d are disposed
30 between the red emitters and green emitters of the first, second, third, and fourth three-color pixel elements, respectively. The red emitters and green emitters are disposed in two pixel rows. Red emitters 170a, 170b, 170c, and 170d are disposed in the first pixel row, to the left of blue emitters 168a, 168b, 168c, and 168d, of the first, second, third, and fourth three-color pixel elements, respectively. Green emitters 172a, 172b, 172c, and 172d are disposed in the
35 second pixel row, to the left of blue emitters 168a, 168b, 168c, and 168d, of the first, second, third, and fourth three-color pixel elements, respectively. Green emitters 174a, 174b, 174c, and 174d are disposed in the first pixel row, to the right of blue emitters 168a, 168b, 168c,

PCT/US01/23892

5 and 168d, of the first, second, third, and fourth three-color pixel elements, respectively. Red emitters 176a, 176b, 176c, and 176d are disposed in the second pixel row, to the right of blue emitters 168a, 168b, 168c, and 168d, of the first, second, third, and fourth three-color pixel elements, respectively.

FIG. 11 is a diagram of an illustrative drive matrix 166 for the three-color pixel
10 element arrangement 164. The illustrative drive matrix 78 shown in FIG. 11 consists of a 2 X 10 drive matrix, where eight column drivers drive the eight red and eight green emitters and two column drivers drive the four blue emitters. A first column driver 178 drives the red emitter 170a and the green emitter 172a. The blue emitters 168a and 168c are tied together and driven by a second column driver 180. A third column driver 182 drives the green
15 emitter 174a and the red emitter 176a, while a fourth column driver 184 drives the red emitter 170b and the green emitter 172b. A fifth column driver 186 drives the blue emitter 168b, which is tied together with 168d. The green emitter 174b and the red emitter 176b are driven by a sixth column driver 188, while a seventh column driver 190 drives red emitter 170c and green emitter 172c. An eighth column driver 192 drives green emitter 174c and red emitter
20 176c, while a ninth column driver 194 drives red emitter 170d and green emitter 172d. Finally, a tenth column driver 196 drives green emitter 174d and red emitter 176d.

The row drivers drive the red, green and blue emitters in each pixel row. Row driver 198 drives red emitters 170a, 170b, 170c, and 170d, green emitters 174a, 174b, 174c, and 174d, as well as blue emitters 168c and 168d. Row driver 200 drives green emitters 172a,
25 172b, 172c, and 172d, red emitters 176a, 176b, 176c, and 176d, and blue emitters 168a and 168b. Each emitter can be driven at continuous luminance values at specific locations in a pixel element, unlike emitters in the prior art, which are driven at discrete luminance values at random locations in a pixel element.

The drive matrix uses approximately 16.6% fewer column drivers to present a given
30 image than does a prior art 2 X 12-drive matrix for the triad arrangement. The column lines are reduced since the blue emitters (168a and 168c; 168b and 168d) are combined. The driver type, voltage, and timing can be the same as already known in the art for each device technology.

Another embodiment of a three-color pixel element arrangement and drive matrix is
35 illustrated in FIGS. 12 and 13. FIG. 12 is an arrangement 201 of eight three-color pixel elements aligned horizontally, four in each array row. Each three-color pixel element can be square-shaped or rectangular-shaped and has two rows with each row including three unit-

WO 02/11112

PCT/US01/23892

5 area polygons, such that an emitter occupies each unit-area polygon. At least one unit-area polygon is at least two times the area of the other unit-area polygons and is occupied by blue emitters 210a, 210b, 210c, 210d, 220a, and 220c. The blue emitters 210a, 210b, 210c, 210d, 220a, and 220c can be formed as a single emitter or can be two separate blue emitters wired together. In this arrangement 201, the blue emitters 210b and 210d are staggered such that a
10 smaller blue emitter (the size of the red and green emitters) will be positioned at the edges of the array vertically aligned with the large blue emitter, as illustrated in FIG. 12. For example, blue emitters 222a, 224a are vertically disposed on either side of the staggered blue emitter 210c and blue emitters 222b, 224b are vertically disposed on either side of the staggered blue emitter 210d.

15 As illustrated in FIG. 12, blue emitters 210a, 210b, 210c, 210d, 220a, 220c, 222a, 222b, 224a, and 224b are disposed between the red emitters and green emitters. Red emitters 202a, 202b, 202c, 202d are disposed in the first pixel row of the first array row and green emitters 204a, 204b, 204c, and 204d are disposed in the second pixel row of the first array row to the left of blue emitters 210a, 210b, 210c & 222a, and 210d & 222b of the first,
20 second, third, and fourth three-color pixel elements, respectively. Green emitters 206a, 206b, 206c, and 206d are disposed in the first pixel row of the first array row and red emitters 208a, 208b, 208c, and 208d are disposed in the second pixel row of the first array row to the right of blue emitters 210c, 210b, 210c & 222a, and 210d & 222b of the first, second, third, and fourth three-color pixel elements, respectively. Red emitters 212a, 212b, 212c, and 212d are
25 disposed in the first pixel row of the second array row and green emitters 214a, 214b, 214c, and 214d are disposed in the second pixel row of the second array row to the left of blue emitters 220a, 220b, 220c & 224a, and 210d & 224b of the first, second, third, and fourth three-color pixel elements, respectively. Green emitters 216a, 216b, 216c, and 216d are disposed in the first pixel row of the second array row and red emitters 218a, 218b, 218c, and
30 218d are disposed in the second pixel row of the second array row to the right of blue emitters 220a, 220b, 220c & 224a, and 210d & 224b of the first, second, third, and fourth three-color pixel elements, respectively. An individual skilled in the art will appreciate that the large blue emitters are staggered throughout the array, which requires having smaller blue emitters at the edges vertically aligned with the larger blue emitters.

35 FIG. 13 is a diagram of an illustrative drive matrix 254 for the three-color pixel element arrangement 201 illustrated in FIG. 12. The illustrative drive matrix 254 shown in FIG. 13 consists of a 2 X 10 drive matrix, where eight column drivers drive the thirty-two red

5 and eight green emitters and two column drivers drive the ten blue emitters. A first column driver 234 drives the red emitters 202a, 212a and the green emitters 204a, 214a. The blue emitters 210a, 220a are tied together with blue emitters 222a, 210c, 224a and are driven by a second column driver 236. A third column driver 238 drives the green emitters 206a, 216a and the red emitters 208a, 218a, while a fourth column driver 240 drives the red emitters 10 202b, 212b and the green emitters 204b, 214b. A fifth column driver 242 drives the blue emitters 210b, 220b, which is tied together with 222b, 210d, 224b. The green emitters 206b, 216b and the red emitters 208b, 218b are driven by a sixth column driver 244, while a seventh column driver 246 drives red emitters 202c, 212c and green emitters 204c, 214c. An eighth column driver 248 drives green emitters 206c, 216c and red emitters 208c, 218c, while 15 a ninth column driver 250 drives red emitters 202d, 212d and green emitters 204d, 214d. Finally, a tenth column driver 252 drives green emitters 206d, 216d and red emitters 208d, 218d.

The row drivers drive the red, green and blue emitters in each pixel row. Row driver 226 drives red emitters 202a, 202b, 202c, and 202d, green emitters 206a, 206b, 206c, and 20 206d, as well as blue emitters 210a, 210b, 222a, 222b. Row driver 228 drives green emitters 204a, 204b, 204c, and 204d, red emitters 208a, 208b, 208c, and 208d, and blue emitters 210c, 210d. Row driver 230 drives red emitters 212a, 212b, 212c, and 212d, green emitters 216a, 216b, 216c, and 216d, as well as blue emitters 220a, 220b. Row driver 232 drives green emitters 214a, 214b, 214c, and 214d, red emitters 218a, 218b, 218c, and 218d, and blue 25 emitters 224a, 224b. Each emitter can be driven at continuous luminance values at specific locations in a three-color pixel element, unlike emitters in the prior art, which are driven at discrete luminance values at random locations in a pixel element.

The drive matrix uses approximately 16.6% fewer column drivers to present a given image than does a prior art 2 X 12-drive matrix for the triad arrangement. The column lines 30 are reduced since the blue emitters (210a, 220a and 210c, 222a, 224a; 210b, 220b and 210d, 222b, 224b) are combined. The driver type, voltage, and timing can be the same as already known in the art for each device technology.

Dot inversion is the preferred method of choice for driving panels having the arrangement of columns and rows as discussed above. Each blue, red and green emitter is 35 driven with alternating polarities. For example, in a first drive event, a red emitter is driven with a positive voltage and at the next drive event, the same red emitter is driven with a negative voltage. In using the arrangements illustrated in FIGS. 6, 8, 10, and 12 that connect

WO 02/11112

PCT/US01/23892

5 the column line of the blue emitter of the first three-color pixel element with its next nearest neighboring three-color pixel element (e.g., the blue emitter of the third three-color pixel element). Likewise, the blue emitter of the second three-color pixel element is coupled with its next nearest neighboring three-color pixel element (e.g., the blue emitter of the fourth three-color pixel element). The "next nearest neighboring" three-color pixel element can be
10 construed as being every other blue emitter of a pair of three-color pixel elements coupled together. For example, the first three-color pixel element is connected with the third three-color pixel element, the second three-color pixel element is connected with the fourth three-color pixel element, the fifth three-color pixel element is connected with the seventh three-color pixel element, the sixth three-color pixel element is connected with the eight three-color
15 pixel element, etc. In this case, any incidence of "flicker" is reduced or eliminated.

In using these arrangements, every column line must be driven with a signal of polarity opposite of its neighbors to guarantee that should any crosstalk occur, it would be the same for each column. If the array is not driven in this way, asymmetrical crosstalk will result in visible artifacts across the screen. Also, nearby red and green emitters of separate
20 pixel elements must be driven by signals of the opposite polarity to ensure that "flicker" will not occur. For example, FIG. 14 illustrates the polarities of the red, green, and blue emitters on the same arrangement in FIG. 6. Here, green emitter 56a (having a negative value) must have an opposite polarity than red emitter 52b (having a positive value). This arrangement eliminates "flicker" since the column line connects one blue emitter with the blue emitter of its next nearest neighboring three-color pixel element. The polarities shown on the blue
25 emitters are those of the column lines, not the polarities stored on the blue emitter. The polarity of the blue emitter is determined by the row that is actively addressing the blue emitter, which is connected to the blue emitter of its next nearest neighboring three-color pixel element.

30 Additional examples illustrating separate dot inversion schemes by the polarities of the red, green, and blue emitters are found in FIGS. 15 and 16. Both FIGS. 15 and 16 are based on the arrangement 114 illustrated in FIG. 8, including another horizontal arrangement (FIG. 15, 115; FIG. 16, 314). In FIG. 15, red emitter 120a (having a positive value) must be driven by signals of an opposite polarity than the polarity of the green emitter 122a (having a
35 negative value). Blue emitter 130a (having a negative value) must be driven by signals of an opposite polarity than the polarity of the blue emitter 132a (having a positive value). Red emitter 124a (having a positive value) must be driven by signals of an opposite polarity than

5 the polarity of the green emitter 126a (having a negative value). The same polarities are duplicated in the additional horizontal arrangement 115. This arrangement also eliminates "flicker" since the column lines connect one blue emitter with the blue emitter of its next nearest neighboring three-color pixel element.

10 In FIG. 16, an alternate dot inversion scheme is illustrated with horizontal arrangement 314. Here, red emitters 120a and 126a and green emitters 122a and 124a (having positive values) must be driven by signals of an opposite polarity than the polarity of the signals driving the red emitters 302a and 308a and green emitters 304a and 306a (having negative values). The same applies for blue emitters 130a and 132a (having positive values) and blue emitters 310a and 312a (having negative values). This arrangement also eliminates
15 "flicker" since the column lines connect one blue emitter with the blue emitter of its next nearest neighboring three-color pixel element.

Another example that illustrates dot inversion by the polarities of the red, green, and blue emitters is found in FIG. 17, which is based on the arrangement 164 illustrated in FIG. 10, including another horizontal arrangement 364. Here, red emitter 170a and green emitter
20 174a (having positive values) and green emitter 172a and red emitter 176a (having negative values) must be driven by signals of the same polarity as red emitter 370a and green emitter 374a (having positive values) and green emitter 372a and red emitter 376a (having negative values), respectively. Blue emitter 168a (having a positive value) must be driven by signals of an opposite polarity than blue emitter 368a (having a negative value). This arrangement
25 also eliminates "flicker" since the column lines connect a blue emitter with the blue emitter of its next nearest neighboring three-color pixel element.

In FIG. 18, an alternate dot inversion scheme is illustrated with horizontal arrangements 164, 264. Here, red emitters 170a, 176a and green emitters 172a, 174a (having positive values) must be driven by signals of an opposite polarity than the polarity of red
30 emitters 370a, 376a and green emitters 372a, 374a (having negative values). The same applies for blue emitter 168a (having a negative value) and blue emitter 368a (having a positive value). This arrangement also eliminates "flicker" since the column lines connect a blue emitter with the blue emitter of its next nearest neighboring three-color pixel element.

Another example that illustrates dot inversion by the polarities of the red, green, and
35 blue emitters is found in FIG. 19, which is based on the arrangement 201 illustrated in FIG. 12. Here, red emitter 202a and green emitter 206a (having positive values) and green emitter 204a and red emitter 208a (having negative values) must be driven by signals of the

WO 02/11112

PCT/US01/23892

5 same polarities as red emitter 212a and green emitter 216a (having positive values) and green emitter 214a and red emitter 218a (having negative values), respectively. Blue emitter 210a (having a positive value with a stored negative value) must be driven by signals of an opposite polarity than blue emitter 220a (having a negative value with a stored positive value). Blue emitter 210c (having a positive value with a stored negative value) must be
10 driven by signals of an opposite polarity than blue emitter 220c (having a negative value with a stored positive value). While blue emitters 222a and 224b must be driven by signals of an opposite polarity than blue emitters 222b and 224a. An individual skilled in the art will appreciate the polarities as described herein. This arrangement also eliminates "flicker" since the column lines connect a blue emitter with the blue emitter of its next nearest
15 neighboring three-color pixel element.

In FIG. 20, an alternate dot inversion scheme is illustrated with horizontal arrangement 201. Here, red emitters 202a, 208a and green emitters 204a, 206a (having positive values) must be driven by signals of an opposite polarity than red emitters 212a, 218a and green emitters 214a, 216a (having negative values). The same applies for blue emitter 210a (having a negative value with a stored positive value) and blue emitter 220a (having a positive value with a stored negative value). Blue emitter 210c (having a negative value with a stored positive value) must be driven by signals of an opposite polarity than blue emitter 220c (having a positive value with a stored negative value). While blue emitters 222a and 224b must be driven by signals of an opposite polarity than blue emitters 222b and 224a.
20 An individual skilled in the art will appreciate the polarities as described herein. This arrangement also eliminates "flicker" since the column lines connect a blue emitter with the blue emitter of its next nearest neighboring three-color pixel element.
25

The three-color pixel element, according to any of the above arrangements, can be operated by appropriately driving the individual emitters. A voltage is applied through each
30 row and column driver to each individual row line and column line. At this point, each emitter is illuminated, according to the proper voltage, to create an image on the display.

By connecting the column lines of one blue emitter with the column line of the blue emitter from the next nearest neighboring three-color pixel element, "flicker" is virtually eliminated while at the same time enabling a reduction in column drivers.

35 While the invention has been described with reference to an exemplary embodiment, it will be understood by those skilled in the art that various changes may be made and equivalents may be substituted for elements thereof without departing from the scope of the

WO 02/01112

PCT/US01/23892

5 invention. In addition, many modifications may be made to adapt a particular situation or material to the teachings without departing from the essential scope thereof. Therefore, it is intended that the invention not be limited to the particular embodiment disclosed as the best mode contemplated for carrying out this invention, but that the invention will include all embodiments falling within the scope of the appended claims.

10

What is claimed is:

5

CLAIMS

1. An array for a display, comprising:
a plurality of row positions and a plurality of column positions;
a plurality of three-color pixel elements, one of said three-color pixel elements
disposed in each of said row positions and said column positions, each of said three-color
10 pixel elements comprising:
a blue emitter disposed at a center of a square disposed at an origin of an X, Y
coordinate system having a first, a second, a third, and a fourth quadrant, wherein said blue
emitter is square-shaped;
a pair of red emitters spaced apart from said blue emitter and symmetrically
15 disposed about said blue emitter in said second and said fourth quadrants, wherein said red
emitters occupy a portion of said second and said fourth quadrants not occupied by said blue
emitter, wherein said red emitters are generally square-shaped having truncated inwardly-
facing corners forming edges parallel to sides of said blue emitter;
a pair of green emitters spaced apart from said blue emitter and symmetrically
20 disposed about said blue emitter in said first and said third quadrants, wherein said green
emitters occupy a portion of said first and said third quadrants not occupied by said blue
emitter, wherein said green emitters are generally square-shaped having truncated inwardly-
facing corners forming edges parallel to said sides of said blue emitter;
a pair of row lines associated with each said row position in said array, a first
25 of said row lines coupled to said red emitters and to said green emitters in said row position
disposed above said origin of said coordinate system in each of said three-color pixel
elements and coupled to said blue emitters of every even pair of adjacent said three-color
pixel elements in said row position, and a second of said row lines coupled to said red
emitters and to said green emitters in said row position disposed below said origin of said
30 coordinate system in each of said three-color pixel elements, and coupled to said blue
emitters of every odd pair of adjacent said three-color pixel elements in said row position;
and
three column lines associated with each said column position in said array, a
first of said column lines coupled to said red emitters and to said green emitters in said
35 column position disposed left of said origin of said rectangular coordinate system in each of
said three-color pixel elements, a second of said column lines coupled to said blue emitter in
said column position disposed at said origin of said rectangular coordinate system in each of

5 said three-color pixel elements, and a third of said column lines coupled to said red emitters and to said green emitters in said column position disposed right of said origin of said rectangular coordinate system in each of said three-color pixel elements, wherein said second column line is coupled to said second column line of a next nearest neighboring said three-color pixel element.

10

2. The array of Claim 1, wherein each said three-color pixel element in a row direction has a spatial frequency greater than a column direction.

3. The array of Claim 1, wherein each said three-color pixel element in a column
15 direction has a spatial frequency greater than in a row direction.

4. The array of Claim 1, wherein each said row line coupled to each said red emitter, said green emitter, and said blue emitter is coupled to a gate of a select transistor,

20 5. The array of Claim 1, wherein each said column line coupled to each said red emitter, said green emitter, and said blue emitter is coupled to a source/drain terminal of a select transistor.

6. The array of Claim 1, wherein said array is driven by dot inversion.

25 7. An array for a display, comprising:
a plurality of row positions and a plurality of column positions;
a plurality of three-color pixel elements, one of said elements disposed in each of said row positions and said column positions, each of said three-color pixel elements comprising:

30 a blue emitter disposed at a center of a square disposed at an origin of an X, Y coordinate system having a first, a second, a third, and a fourth quadrant, wherein said blue emitter is square-shaped;

a pair of red emitters spaced apart from said blue emitter and symmetrically disposed about said blue emitter in said second and said fourth quadrants, wherein said red
35 emitters occupy a portion of said second and said fourth quadrants not occupied by said blue emitter, wherein said red emitters are L-shaped;

WO 02/11112

PCT/US01/23892

5 a pair of green emitters spaced apart from said blue emitter and symmetrically disposed about said blue emitter in said first and said third quadrants, wherein said green emitters occupy a portion of said first and said third quadrants not occupied by said blue emitter, wherein said green emitters are L-shaped;

10 a pair of row lines associated with each said row position in said array, a first of said row lines coupled to said red emitters and to said green emitters in said row position disposed above said origin of said coordinate system in each of said three-color pixel elements and coupled to said blue emitters of every even pair of adjacent said three-color pixel elements in said row position, and a second of said row lines coupled to said red emitters and to said green emitters in said row position disposed below said origin of said coordinate system in each of said three-color pixel elements and coupled to said blue emitters of every odd pair of adjacent said three-color pixel elements in said row position; and

15 three column lines associated with each said column position in said array, a first of said column lines coupled to said red emitters and to said green emitters in said column position disposed left of said center of said square in each of said three-color pixel elements, a second of said column lines coupled to said blue emitter in said column position disposed at said center of said square in each of said three-color pixel elements, and a third of said column lines coupled to said red emitters and to said green emitters in said column position disposed right of said center of said square in each of said three-color pixel elements, wherein said second column line is coupled to said second column line of a next nearest neighboring said three-color pixel element.

20 8. The array of Claim 7, wherein each said three-color pixel element in a row direction has a spatial frequency greater than in a column direction.

25 9. The array of Claim 7, wherein each said three-color pixel element in a column direction has a spatial frequency greater than in a row direction.

10. The array of Claim 7, wherein each said row line coupled to each said red emitter, said green emitter, and said blue emitter is coupled to a gate of a select transistor.

35 11. The array of Claim 7, wherein each said column line coupled to each said red emitter, said green emitter, and said blue emitter is coupled to a source/drain terminal of a select transistor.

5

12. The array of Claim 7, wherein said array is driven by dot inversion.

13. An array of three-color pixel elements, comprising:

10 a row comprising first, second, third, and fourth three-color pixel elements,
each three-color pixel element comprising a blue emitter disposed at a center of a square
disposed at an origin of an X, Y coordinate system having a first, a second, a third, and a
fourth quadrant, wherein said blue emitter is square-shaped, a pair of red emitters spaced
15 apart from said blue emitter and symmetrically disposed about said blue emitter in said
second and said fourth quadrants, wherein said red emitters occupy a portion of said second
and said fourth quadrants not occupied by said blue emitter, wherein said red emitters are
generally square-shaped having truncated inwardly facing corners forming edges parallel to
sides of said blue emitter, and a pair of green emitters spaced apart from said blue emitter and
20 symmetrically disposed about said blue emitter in said first and said third quadrants, wherein
said green emitters occupy a portion of said first and said third quadrants not occupied by
said blue emitter, wherein said green emitters are generally square-shaped having truncated
inwardly-facing corners forming edges parallel to said sides of said blue emitter;

first and second row line drivers coupled to each said three-color pixel
elements;

25 a first row line coupled to said first row line driver, said first row line coupled
to said blue emitter of said third and said fourth three-color pixel elements and to a first red
emitter and a first green emitter of said first, second, third, and fourth three-color pixel
elements;

30 a second row line coupled to said second row line driver, said second row line
coupled to said blue emitter of said first and said second three-color pixel elements and to a
second red emitter and said a green emitter of said first, second, third, and fourth three-color
pixel elements;

first through tenth column line drivers coupled to each of said three-color
pixel elements;

35 a first column line coupled to said first column line driver, said first column
line coupled to said first red emitter and said second green emitter of said first three-color
pixel element;

- 5 a second column line coupled to said second column line driver, said second column line coupled to said blue emitter of said first three-color pixel element and to an eighth column line coupled to said blue emitter of said third three-color pixel element;
- a third column line coupled to said third column line driver, said third column line coupled to said second red emitter and said first green emitter of said first three-color pixel element;
- 10 a fourth column line coupled to said fourth column line driver, said fourth column line coupled to said first red emitter and said second green emitter of said second three-color pixel element;
- a fifth column line coupled to said fifth column line driver, said fifth column line coupled to said blue emitter of said second three-color pixel element and to an eleventh column line coupled to said blue emitter of said fourth three-color pixel element;
- 15 a sixth column line coupled to said sixth column line driver, said sixth column line coupled to said second red emitter and said first green emitter of said second three-color pixel element;
- a seventh column line coupled to said seventh column line driver, said seventh column line coupled to said first red emitter and said second green emitter of said third three-color pixel element;
- 20 a ninth column line coupled to said eighth column line driver, said ninth column line coupled to said second red emitter and said first green emitter of said fourth three-color pixel element;
- a tenth column line coupled to said ninth column line driver, said tenth column line coupled to said first red emitter and said second green emitter of said fourth three-color pixel element; and
- 25 a twelfth column line coupled to said tenth column line driver, said tenth column line coupled to said second red emitter and said first green emitter of said fourth three-color pixel element.

14. The array of Claim 13, wherein said array is driven by dot inversion.

35 15. The array of Claim 13, wherein each said row line coupled to each said red emitter, said green emitter, and said blue emitter is coupled to a gate of a select transistor.

5 16. The array of Claim 13, wherein each said column line coupled to each said red emitter, said green emitter, and said blue emitter is coupled to a source/drain terminal of a select transistor.

10 17. The array of Claim 13, further comprising another blue emitter in each said three color pixel element.

15 18. An array of three-color pixel elements, comprising:
 a row comprising first, second, third, and fourth three-color pixel elements, each three-color pixel element comprising a blue emitter disposed at a center of a square
 disposed at an origin of an X, Y coordinate system having a first, a second, a third, and a
 fourth quadrant, wherein said blue emitter is square-shaped, a pair of red emitters spaced
 apart from said blue emitter and symmetrically disposed about said blue emitter in said
 second and said fourth quadrants, wherein said red emitters occupy a portion of said second
 and said fourth quadrants not occupied by said blue emitter, wherein said red emitters are L-
 shaped, and a pair of green emitters spaced apart from said blue emitter and symmetrically
 disposed about said blue emitter in said first and said third quadrants, wherein said green
 emitters occupy a portion of said first and said third quadrants not occupied by said blue
 emitter, wherein said green emitters are T-shaped

20 first and second row line drivers coupled to each of said three-color pixel
25 elements;

 a first row line coupled to said first row line driver, said first row line coupled
 to said blue emitter of said third and said fourth three-color pixel element and to a first red
 emitter and a first green emitter of said first, second, third, and fourth three-color pixel
 elements;

30 a second row line coupled to said second row line driver, said second row line
 coupled to said blue emitter of said first and said second three-color pixel element and to a
 second red emitter and a second green emitter of said first, second, third, and fourth three-
 color pixel elements;

35 first through tenth column line drivers coupled to each of said three-color
 pixel elements;

WO 02/11112

PCT/US01/73892

5 a first column line coupled to said first column line driver, said first column line coupled to said first red emitter and said second green emitter of said first three-color pixel element;

a second column line coupled to said second column line driver, said second column line coupled to said blue emitter of said first three-color pixel element and to an eighth column line coupled to said blue emitter of said third three-color pixel element;

10 a third column line coupled to said third column line driver, said third column line coupled to said second red emitter and said first green emitter of said first three-color pixel element;

a fourth column line coupled to said fourth column line driver, said fourth column line coupled to said first red emitter and said second green emitter of said second three-color pixel element;

a fifth column line coupled to said fifth column line driver, said fifth column line coupled to said blue emitter of said second three-color pixel element and to an eleventh column line coupled to said blue emitter of said fourth three-color pixel element;

20 a sixth column line coupled to said sixth column line driver, said sixth column line coupled to said second red emitter and said first green emitter of said second three-color pixel element;

a seventh column line coupled to said seventh column line driver, said seventh column line coupled to said first red emitter and said second green emitter of said third three-color pixel element;

25 a ninth column line coupled to said eighth column line driver, said ninth column line coupled to said second red emitter and said first green emitter of said third three-color pixel element;

a tenth column line coupled to said ninth column line driver, said tenth column line coupled to said first red emitter and said second green emitter of said fourth three-color pixel element; and

30 a twelfth column line coupled to said tenth column line driver, said tenth column line coupled to said second red emitter and said first green emitter of said fourth three-color pixel element

35

19 The array of Claim 18, wherein said array is driven by dot inversion.

WO 02/11112

PCT/US01/23892

- 5 20. The array of Claim 18, wherein each said row line coupled to each said red emitter, said green emitter, and said blue emitter is coupled to a gate of a select transistor.
21. The array of Claim 18, wherein each said column line coupled to each said red emitter, said green emitter, and said blue emitter is coupled to a source/drain terminal of a
10 select transistor.
22. The array of Claim 18, further comprising another blue emitter in each said three-color pixel element.
- 15 23. A three-color pixel element for a display, comprising:
 first and second pixel rows, each pixel row including three unit-area polygons,
 wherein an emitter occupies each said unit-area polygon;
 wherein a red emitter occupies a left unit-area polygon in said first pixel row
 and a green emitter occupies a right unit-area polygon in said first pixel row;
20 wherein a green emitter occupies a left unit-area polygon in said second pixel
 row and a red emitter occupies a right unit-area polygon in said second pixel row; and
 wherein a blue emitter occupies a center unit-area polygon in both said first
 and said second pixel rows.
- 25 24. The three-color pixel element of Claim 23, wherein said green emitter occupies said left unit-area polygon in said first pixel row and said red emitter occupies said right unit-area polygon in said first pixel row; and wherein said red emitter occupies said left unit-area polygon in said second pixel row and said green emitter occupies said right unit-area polygon in said second pixel row.
- 30 25. The three-color pixel element of Claim 23, wherein said unit-area polygon is a square.
26. The three-color pixel element of Claim 23, wherein said unit-area polygon is a
35 rectangle.

WO 02/11112

PCT/US01/23892

5 27. The three-color pixel element of Claim 23, wherein said blue emitters occupying said center unit-area polygon in both said first and said second pixel rows are wired together.

10 28. An array for a display, comprising:
a plurality of array row positions and a plurality of column positions;
a plurality of three-color pixel elements, one of said three-color pixel elements disposed in each of said row positions and said column positions, each of said three-color pixel elements comprising:

15 first and second pixel rows, each pixel row including three unit-area polygons, wherein an emitter occupies each said unit-area polygon, wherein a red emitter occupies a left unit-area polygon in said first pixel row and a green emitter occupies a right unit-area polygon in said first pixel row, wherein a green emitter occupies a left unit-area polygon in said second pixel row and a red emitter occupies a right unit-area polygon in said second pixel row, and wherein a blue emitter occupies a center unit-area polygon in both said first and said second pixel rows;

20 a plurality of row lines associated with each said row position in said array, a first of said row lines coupled to said blue emitter in said first pixel row, to said red emitters in said first pixel row and to said green emitters in said first pixel row in each of said three-color pixel elements in said array row position, wherein said first of said row lines is coupled to said blue emitters in said first pixel row of every even pair of adjacent said three-color pixel elements, and a second of said row lines coupled to said blue emitter in said second pixel row, to said red emitters in said second pixel row, and to said green emitters in said second pixel row in each of said three-color pixel elements in said array row position, wherein said second of said row lines is coupled to said blue emitters in said second row of every odd pair of adjacent said three-color pixel elements; and

25 a plurality of column lines associated with each said column position, a first of said column lines coupled to said red emitters and to said green emitters in said column position disposed left of said blue emitters in each of said three color pixel elements, a second of said column lines coupled to said blue emitters in said column position disposed at said center of square in each of said three-color pixel elements, and a third of said column lines coupled to said red emitters and to said green emitters in said column position disposed right of said blue emitters in each of said three-color pixel elements, wherein said second

- 5 column line is coupled to said second column line of a next nearest neighboring said three-color pixel element.

29. The array of Claim 28, wherein each said three-color pixel element in a row
10 direction has a spatial frequency greater than in a column direction.

30. The array of Claim 28, wherein each said three-color pixel element in a
column direction has a spatial frequency greater than in a row direction.

31. The array of Claim 28, wherein each said row line coupled to each said red
15 emitter, said green emitter, and said blue emitter is coupled to a gate of a select transistor.

32. The array of Claim 28, wherein each said column line coupled to each said red
emitter, said green emitter, and said blue emitter is coupled to a source/drain terminal of a
select transistor.

33. The array of Claim 28, wherein said array is driven by dot inversion.

34. The array of Claim 28, wherein said green emitter occupies said left unit-area
25 polygon in said first pixel row and said red emitter occupies said right unit-area polygon in
said first pixel row; and wherein said red emitter occupies said left unit-area polygon in said
second pixel row and said green emitter occupies said right unit-area polygon in said second
pixel row.

35. The array of Claim 28, wherein said unit-area polygon is a square.

36. The array of Claim 28, wherein said unit-area polygon is a rectangle.

37. The array of Claim 28, wherein said blue emitters occupying said center unit-
35 area polygon in both said first and said second pixel rows are wired together.

38. An array of three-color pixel elements, comprising:

WO 02/01112

PCT/US01/23892

5 an array row comprising first, second, third, and fourth three-color pixel elements, each said three-color pixel element comprising first and second pixel rows, each pixel row including three unit-area polygons, wherein an emitter occupies each said unit-area polygon, wherein a red emitter occupies a left unit-area polygon in said first pixel row and a green emitter occupies a right unit-area polygon in said first pixel row, wherein a green emitter occupies a left unit-area polygon in said second pixel row and a red emitter occupies a right unit-area polygon in said second pixel row, and wherein a blue emitter occupies a center unit-area polygon in both said first and said second pixel rows;

10 first and second row line drivers coupled to each said three-color pixel elements;

15 a first row line coupled to said first row line driver, said first row line coupled to said blue emitters in said first pixel row of said third and said fourth three-color pixel element and to said red emitter and said green emitter in said first pixel row of said first, second, third, and fourth three-color pixel elements;

20 a second row line coupled to said second row line driver, said second row line coupled to said blue emitters in said second pixel row of said first and said second three-color pixel element and to said red emitter and said green emitter in said second pixel row of said first, second, third, and fourth three-color pixel elements;

first through tenth column line drivers coupled to each said three-color pixel elements;

25 a first column line coupled to said first column line driver, said first column line coupled to said red emitter in said first pixel row and said green emitter in said second pixel row of said first three color pixel element;

30 a second column line coupled to said second column line driver, said second column line coupled to said blue emitters of said first three-color pixel element and to an eighth column line coupled to said blue emitters of said third three-color pixel element;

a third column line coupled to said third column line driver, said third column line coupled to said red emitter in said second pixel row and said green emitter in said first pixel row of said first three-color pixel element;

35 a fourth column line coupled to said fourth column line driver, said fourth column line coupled to said red emitter in said first pixel row and said green emitter in said second pixel row of said second three-color pixel element;

5 a fifth column line coupled to said fifth column line driver, said fifth column line coupled to said blue emitters of said second three-color pixel element and to an eleventh column line coupled to said blue emitters of said fourth three-color pixel element;

a sixth column line coupled to said sixth column line driver, said sixth column line coupled to said red emitter in said second pixel row and said green emitter in said first pixel row of said second three-color pixel element;

a seventh column line coupled to said seventh column line driver, said seventh column line coupled to said red emitter in said first pixel row and said green emitter in said second pixel row of said third three-color pixel element;

15 a ninth column line coupled to said eighth column line driver, said ninth column line coupled to said red emitter in said second pixel row and said green emitter in said first pixel row of said fourth three-color pixel element;

a tenth column line coupled to said ninth column line driver, said tenth column line coupled to said red emitter in said first pixel row and said green emitter in said second pixel row of said fourth three-color pixel element; and

20 a twelfth column line coupled to said tenth column line driver, said tenth column line coupled to said red emitter in said second pixel row and said green emitter in said first pixel row of said fourth three-color pixel element.

25 39. The array of Claim 38, wherein said array is driven by dot inversion.

40. The array of Claim 38, wherein each said row line coupled to each said red emitter, said green emitter, and said blue emitter is coupled to a gate of a select transistor.

30 41. The array of Claim 38, wherein each said column line coupled to each said red emitter, said green emitter, and said blue emitter is coupled to a source/drain terminal of a select transistor.

35 42. The array of Claim 38, wherein said green emitter occupies said left unit-area polygon in said first row and said red emitter occupies said right unit-area polygon in said first row; and wherein said red emitter occupies said left unit-area polygon in said first row and said green emitter occupies said right unit-area polygon in said first row.

- 5 43. The array of Claim 38, wherein said unit-area polygon is a square.
44. The array of Claim 38, wherein said unit-area polygon is a rectangle.
45. The array of Claim 38, wherein said blue emitters occupying said center unit-
10 area polygon in both said first and said second rows are wired together.
46. An array for a display, comprising:
 a plurality of array row positions and a plurality of column positions;
 a plurality of three-color pixel elements, one of said three-color pixel elements
15 disposed in each of said row positions and said column positions, each of said three-color
pixel elements comprising:
 first and second pixel rows, each pixel row including three unit-area polygons,
 wherein an emitter occupies each said unit-area polygon, wherein a red emitter occupies a left
 unit-area polygon in said first pixel row and a green emitter occupies a right unit-area
20 polygon in said first pixel row; wherein a green emitter occupies a left unit-area polygon in
said second pixel row and a red emitter occupies a right unit-area polygon in said second
pixel row; and wherein a single blue emitter occupies both center unit-area polygons in said
first and said second pixel rows;
 a plurality of row lines associated with each said row position in said array, a
25 first of said row lines coupled to said blue emitter, to said red emitters, and to said green
emitters in said first pixel row in each of said three-color pixel elements in said array row
position, wherein said first of said row lines is coupled to said blue emitters of every even
pair of adjacent said three-color pixel elements, and a second of said row lines coupled to
said blue emitter, to said red emitters, and to said green emitters in said second pixel row in
30 each of said three-color pixel elements in said array row position, wherein said second of said
row lines is coupled to said blue emitters of every odd pair of adjacent said three-color pixel
elements; and
 a plurality of column lines associated with each said column position in said
array, a first of said column lines coupled to said red emitters and to said green emitters in
35 said column position disposed left of said blue emitter in each of said three-color pixel
elements, a second of said column lines coupled to said blue emitter in said column position
in each of said three-color pixel elements, and a third of said column lines coupled to said red

PCT/US01/23892

5 emitters and to said green emitters in said column position disposed right of said blue emitter in each of said three-color pixel elements, wherein said second column line is coupled to said second column line of a next nearest neighboring said three-color pixel element.

47. The array of Claim 46, wherein each said three-color pixel element in a row
10 direction has a spatial frequency greater than in a column direction.

48. The array of Claim 46, wherein each said three-color pixel element in a column direction has a spatial frequency greater than in a row direction.

15 49. The array of Claim 46, wherein each said row line coupled to each said red emitter, said green emitter, and said blue emitter is coupled to a gate of a select transistor.

50. The array of Claim 46, wherein each said column line coupled to each said red emitter, said green emitter, and said blue emitter is coupled to a source/drain terminal of a
20 select transistor.

51. The array of Claim 46, wherein said array is driven by dot inversion.

25 52. The array of Claim 46, wherein said green emitter occupies said left unit-area polygon in said first pixel row and said red emitter occupies said right unit-area polygon in said first pixel row; and wherein said red emitter occupies said left unit-area polygon in said second pixel row and said green emitter occupies said right unit-area polygon in said second pixel row.

30 53. The array of Claim 46, wherein said unit area polygon is a square.

54. The array of Claim 46, wherein said unit-area polygon is a rectangle.

35 55. An array of three-color pixel elements, comprising:
an array row comprising first, second, third, and fourth three-color pixel elements, each three-color pixel element comprising first and second pixel rows, each pixel row including three unit-area polygons, wherein an emitter occupies each said unit-area

5 polygon, wherein a red emitter occupies a left unit area polygon in said first pixel row and a green emitter occupies a right unit-area polygon in said first pixel row; wherein a green emitter occupies a left unit area polygon in said second pixel row and a red emitter occupies a right unit-area polygon in said second pixel row; and wherein a single blue emitter occupies both center unit-area polygons in said first and said second pixel rows;

10 first and second row line drivers coupled to each of said three-color pixel elements;

a first row line coupled to said first row line driver, said first row line coupled to said blue emitters of said third and said fourth three-color pixel element and to said red emitter and said green emitter in said first pixel row of said first, second, third, and fourth
15 three-color pixel elements;

a second row line coupled to said second row line driver, said second row line coupled to said blue emitters of said first and said second three-color pixel element and to said red emitter and said green emitter in said second pixel row of said first, second, third, and fourth three-color pixel elements;

20 first through tenth column line drivers coupled to each of said three-color pixel elements;

a first column line coupled to said first column line driver, said first column line coupled to said red emitter in said first pixel row and said green emitter in said second pixel row of said first three-color pixel element;

25 a second column line coupled to said second column line driver, said second column line coupled to said blue emitter of said first three-color pixel element and to an eighth column line coupled to said blue emitter of said third three-color pixel element;

a third column line coupled to said third column line driver, said third column line coupled to said red emitter in said second pixel row and said green emitter in said first
30 pixel row of said first three color pixel element;

a fourth column line coupled to said fourth column line driver, said fourth column line coupled to said red emitter in said first pixel row and said green emitter in said second pixel row of said second three-color pixel element;

a fifth column line coupled to said fifth column line driver, said fifth column line coupled to said blue emitter of said second three-color pixel element and to an eleventh
35 column line coupled to said blue emitter of said fourth three-color pixel element;

5 a sixth column line coupled to said sixth column line driver, said sixth column line coupled to said red emitter in said second pixel row and said green emitter in said first pixel row of said second three-color pixel element;

a seventh column line coupled to said seventh column line driver, said seventh column line coupled to said red emitter in said first pixel row and said green emitter in said second pixel row of said third three-color pixel element;

10 a ninth column line coupled to said eighth column line driver, said ninth column line coupled to said red emitter in said second pixel row and said green emitter in said first pixel row of said fourth three-color pixel element;

a tenth column line coupled to said ninth column line driver, said tenth column line coupled to said red emitter in said first pixel row and said green emitter in said second pixel row of said fourth three-color pixel element; and

15 a twelfth column line coupled to said tenth column line driver, said tenth column line coupled to said red emitter in said second pixel row and said green emitter in said first pixel row of said fourth three-color pixel element.

20

56. The array of Claim 55, wherein said array is driven by dot inversion.

57. The array of Claim 55, wherein each said row line coupled to each said red emitter, said green emitter, and said blue emitter is coupled to a gate of a select transistor.

25

58. The array of Claim 55, wherein each said column line coupled to each said red emitter, said green emitter, and said blue emitter is coupled to a source/drain terminal of a select transistor.

30

59. The array of Claim 55, wherein said green emitter occupies said left unit-area polygon in said first pixel row and said red emitter occupies said right unit area polygon in said first pixel row; and wherein said red emitter occupies said left unit area polygon in said second pixel row and said green emitter occupies said right unit-area polygon in said second pixel row.

35

60. The array of Claim 55, wherein said unit-area polygon is a square.

WO 02/11112

PCT/US01/23892

5 61. The array of Claim 55, wherein said unit-area polygon is a rectangle.

 62. An array for a display, comprising:
 a plurality of array row positions and a plurality of column positions;
 a plurality of three-color pixel elements, one of said three-color pixel elements
10 disposed in each of said array row positions and said column positions, wherein each of said
 three-color pixel elements comprises:

 first and second pixel rows, each row including three unit-area polygons,
 wherein an emitter occupies each said unit area polygon, wherein a red emitter occupies a left
 unit-area polygon in said first pixel row and a green emitter occupies a right unit-area
15 polygon in said first pixel row; wherein a green emitter occupies a left unit-area polygon in
 said first pixel row and a red emitter occupies a right unit-area polygon in said first pixel row;
 and wherein a single blue emitter occupies both center unit-area polygons in said first and
 said second pixel rows;

 wherein adjacent horizontal pairs of said three-color pixel elements are
20 vertically offset from one another by one pixel row;

 a plurality of row lines associated with each said array row position,
 wherein a first of said row lines is coupled to all said red and said green
 emitters in said first pixel row of each odd pair of said three-color pixel elements in each said
 array row position and to all said red and said green emitters in said second pixel row of each
25 even pair of said three-color pixel elements in each said array row position, wherein said first
 of said row lines is coupled to said blue emitters of every odd pair of adjacent said three-color
 pixel elements;

 wherein a second of said row lines is coupled to all said red and said green
 emitters in said second pixel row of each odd pair of said three-color pixel elements in each
30 said array row position and to all said red and said green emitters in said first pixel row of
 each even pair of said three-color pixel elements in each said array row position, wherein said
 first of said row lines is coupled to said blue emitters of every even pair of adjacent said
 three-color pixel elements; and

 a plurality of column lines associated with each said column position in said
35 array;

5 wherein a first, a fourth, a seventh, and a tenth of said column lines is coupled to said red emitters and to said green emitters in said column position disposed left of said blue emitter in each of said three-color pixel elements;

10 wherein a second, a fifth, an eighth, and an eleventh of said column lines is coupled to said blue emitter in said column position in each of said three-color pixel elements, wherein said second of said column lines is coupled to said eighth of said column lines and wherein said fifth of said column lines is coupled to said eleventh of said column lines; and

15 wherein a third, a sixth, a ninth, and a twelfth of said column lines is coupled to said red emitters and to said green emitters in said column position disposed right of said blue emitter in each of said three-color pixel elements.

63. The array of Claim 62, wherein each said three-color pixel element in a row direction has a spatial frequency greater than in a column direction.

20 64. The array of Claim 62, wherein each said three-color pixel element in a column direction has a spatial frequency greater than in a row direction.

25 65. The array of Claim 62, wherein each said row line coupled to each said red emitter, said green emitter, and said blue emitter is coupled to a gate of a select transistor.

66. The array of Claim 62, wherein each said column line coupled to each said red emitter, said green emitter, and said blue emitter is coupled to a source/drain terminal of a select transistor.

30 67. The array of Claim 62, wherein said array is driven by dot inversion.

35 68. The array of Claim 62, wherein said green emitter occupies said left unit-area polygon in said first pixel row and said red emitter occupies said right unit-area polygon in said first pixel row; and wherein said red emitter occupies said left unit-area polygon in said second pixel row and said green emitter occupies said right unit-area polygon in said second pixel row.

WO 02/11112

PCT/US01/23892

5 69. The array of Claim 62, wherein said unit-area polygon is a square.

 70. The array of Claim 62, wherein said unit-area polygon is a rectangle.

 71. An array of three-color pixel elements, comprising:
10 a plurality of array rows and a plurality of array columns containing three-
color pixel elements, each said three-color pixel element comprising first and second pixel
rows, each pixel row including three unit-area polygons, wherein an emitter occupies each
said unit area polygon, wherein a red emitter occupies a left unit-area polygon in said first
pixel row and a green emitter occupies a right unit-area polygon in said first pixel row;
15 wherein a green emitter occupies a left unit-area polygon in said second pixel row and a red
emitter occupies a right unit-area polygon in said second pixel row; and wherein a single blue
emitter occupies both center unit-area polygons in said first and said second pixel rows;

 wherein adjacent horizontal pairs of said three-color pixel elements are
vertically offset from one another by one pixel row;

20 first and second row line drivers coupled to each of said three-color pixel
elements;

 a first row line coupled to said first row line driver, wherein said first row line
is coupled to all said red and said green emitters in said first pixel row of each odd pair of
said three-color pixel elements in each said array row position and to all said red and said
25 green emitters in said second pixel row of each even pair of said three-color pixel elements in
each said array row position, wherein said first of said row lines is coupled to said blue
emitters of every odd pair of adjacent said three-color pixel elements;

 a second row line coupled to said second row line driver, wherein said second
row line is coupled to all said red and said green emitters in said second pixel row of each
30 odd pair of said three-color pixel elements in each said array row position and to all said red
and said green emitters in said first pixel row of each even pair of said three-color pixel
elements in each said array row position, wherein said first of said row lines is coupled to
said blue emitters of every even pair of adjacent said three color pixel elements; and

35 first through tenth column line drivers coupled to each of said three-color
pixel elements;

WO 02/11112

PCT/US01/23892

5 a first column line coupled to said first column line driver, said first column line coupled to all left-most emitters of every said three-color pixel element in a first of said array columns;

 a second column line coupled to said second column line driver, said second column line coupled to all center emitters of every said three-color pixel element in a second of said array columns and to an eighth column line coupled to all center emitters of every said three-color pixel element in an eighth of said array columns;

 a third column line coupled to said third column line driver, said third column line coupled to all right-most emitters of every said three-color pixel element in a third of said array columns;

15 a fourth column line coupled to said fourth column line driver, said fourth column line coupled to all left-most emitters of every said three-color pixel element in a fourth of said array columns;

 a fifth column line coupled to said fifth column line driver, said fifth column line coupled to all center emitters of every said three-color pixel element in a fifth of said array columns and to an eleventh column line coupled to all center emitters of every said three-color pixel element in an eleventh of said array columns;

 a sixth column line coupled to said sixth column line driver, said sixth column line coupled to all right-most emitters of every said three-color pixel element in a sixth of said array columns;

25 a seventh column line coupled to said seventh column line driver, said seventh column line coupled to all left-most emitters of every said three-color pixel element in a seventh of said array columns;

 a eighth column line coupled to said eighth column line driver, said eighth column line coupled to all right-most emitters of every said three-color pixel element in a ninth of said array columns;

30 a tenth column line coupled to said ninth column line driver, said tenth column line coupled to all left-most emitters of every said three-color pixel element in a tenth of said array columns; and

 a twelfth column line coupled to said tenth column line driver, said twelfth column line coupled to all right-most emitters of every said three-color pixel element in a twelfth of said array columns.

WO 02/11112

PCT/US01/23892

5 72. The array of Claim 71, wherein said array is driven by dot inversion.

 73. The array of Claim 71, wherein each said row line coupled to each said red emitter, said green emitter, and said blue emitter is coupled to a gate of a select transistor.

10 74. The array of Claim 71, wherein each said column line coupled to each said red emitter, said green emitter, and said blue emitter is coupled to a source/drain terminal of a select transistor.

 75. The array of Claim 71, wherein said green emitter occupies said left unit-area polygon in said first pixel row and said red emitter occupies said right unit-area polygon in said first pixel row; and wherein said red emitter occupies said left unit-area polygon in said second pixel row and said green emitter occupies said right unit-area polygon in said second pixel row.

20 76. The array of Claim 71, wherein said unit-area polygon is a square.

 77. The array of Claim 71, wherein said unit-area polygon is a rectangle.

25 78. A method of driving a three-color pixel element in a display, comprising:
 providing a three-color pixel element comprising a blue emitter disposed at a center of a square disposed at an origin of an X, Y coordinate system having a first, a second, a third, and a fourth quadrant, wherein said blue emitter is square-shaped, a pair of red emitters spaced apart from said blue emitter and symmetrically disposed about said blue emitter in said second and said fourth quadrants, wherein said red emitters occupy a portion
30 of said second and said fourth quadrants not occupied by said blue emitter, wherein said red emitters are generally square-shaped having truncated inwardly-facing corners forming edges parallel to sides of said blue emitter, and a pair of green emitters spaced apart from said blue emitter and symmetrically disposed about said blue emitter in said first and said third quadrants, wherein said green emitters occupy a portion of said first and said third quadrants not occupied by said blue emitter, wherein said green emitters are generally square-shaped having truncated inwardly-facing corners forming edges parallel to said sides of said blue emitter; and
35

WO 02/11112

PCF/US01/23892

5 driving said blue emitter, said red emitters, and said green emitters, wherein said blue emitter of said three-color pixel element is coupled to a blue emitter of a next nearest neighboring three-color pixel element.

10 79. A method of driving a three-color pixel element in a display, comprising:
providing a three-color pixel element comprising a blue emitter disposed at a center of a square disposed at an origin of an X, Y coordinate system having a first, a second, a third, and a fourth quadrant, wherein said blue emitter is square-shaped, a pair of red emitters spaced apart from said blue emitter and symmetrically disposed about said blue emitter in said second and said fourth quadrants, wherein said red emitters occupy a portion of said second and said fourth quadrants not occupied by said blue emitter, wherein said red emitters are L-shaped, and a pair of green emitters spaced apart from said blue emitter and symmetrically disposed about said blue emitter in said first and said third quadrants, wherein said green emitters occupy a portion of said first and said third quadrants not occupied by said blue emitter, wherein said green emitters are L-shaped; and

15 20 driving said blue emitter, said red emitters, and said green emitters, wherein said blue emitter of said three-color pixel element is coupled to a blue emitter of a next nearest neighboring three-color pixel element.

25 80. A method of driving a three-color pixel element in a display, comprising:
providing a three-color pixel element comprising first and second pixel rows, each pixel row including three unit-area polygons, wherein an emitter occupies each said unit-area polygon, wherein a red emitter occupies a left unit-area polygon in said first pixel row and a green emitter occupies a right unit-area polygon in said first pixel row, wherein a green emitter occupies a left unit-area polygon in said second pixel row and a red emitter occupies a right unit-area polygon in said second pixel row, and wherein a blue emitter occupies a center unit-area polygon in both said first and said second pixel rows; and

30 driving said blue emitters, said red emitters, and said green emitters, wherein said blue emitters of said three-color pixel element is coupled to a pair of blue emitters of a next nearest neighboring three-color pixel element.

35 81. The method of Claim 80, wherein said green emitter occupies said left unit-area polygon in said first pixel row and said red emitter occupies said right unit-area polygon

WO 02/11112

PC 170501/23892

5 in said first pixel row; and wherein said red emitter occupies said left unit-area polygon in said second pixel row and said green emitter occupies said right unit-area polygon in said second pixel row.

10 82. A method of driving a three-color pixel element in a display, comprising:
providing a three-color pixel element comprising first and second pixel rows,
each pixel row including three unit-area polygons, wherein an emitter occupies each said
unit-area polygon, wherein a red emitter occupies a left unit-area polygon in said first pixel
row and a green emitter occupies a right unit-area polygon in said first pixel row; wherein a
green emitter occupies a left unit-area polygon in said second pixel row and a red emitter
15 occupies a right unit-area polygon in said second pixel row; and wherein a single blue emitter
occupies both center unit-area polygons in said first and said second pixel rows; and
driving said blue emitter, said red emitters, and said green emitters, wherein
said blue emitter of said three-color pixel element is coupled to a blue emitter of a next
nearest neighboring three-color pixel element.

20 83. The method of Claim 82, wherein said green emitter occupies said left unit-
area polygon in said first pixel row and said red emitter occupies said right unit-area polygon
in said first pixel row; and wherein said red emitter occupies said left unit-area polygon in
said second pixel row and said green emitter occupies said right unit-area polygon in said
second pixel row.

25 84. A method of driving a three-color pixel element in a display, comprising:
providing a three-color pixel element comprising first and second pixel rows,
each pixel row including three unit-area polygons, wherein an emitter occupies each said
unit-area polygon, wherein a red emitter occupies a left unit-area polygon in said first pixel
row and a green emitter occupies a right unit-area polygon in said first pixel row; wherein a
30 green emitter occupies a left unit-area polygon in said second pixel row and a red emitter
occupies a right unit-area polygon in said second pixel row; wherein a single blue emitter
occupies both center unit-area polygons in said first and said second pixel rows; and wherein
adjacent horizontal pairs of said three-color pixel elements are vertically offset from one
another by one pixel row; and

5 driving said blue emitter, said red emitters, and said green emitters, wherein said blue emitter of said three-color pixel element is coupled to a blue emitter of a next nearest neighboring three-color pixel element.

10 85. The method of Claim 84, wherein said green emitter occupies said left unit-area polygon in said first pixel row and said red emitter occupies said right unit-area polygon in said first pixel row; and wherein said red emitter occupies said left unit-area polygon in said second pixel row and said green emitter occupies said right unit-area polygon in said second pixel row.

WO 02/11112

1/19

PCT/US01/23892




FIG. 1






FIG. 2

WO 02/11112

7/19

PCT/US01/23892






WO 02/11112

4/19


PCT/US01/23892



WO 02/11112

5/19

PCT/US01/23892






FIG. 7

WO 02/01112

7/19

PCT/US01/23892





FIG. 8

WO 02/11112

8/19


PCT/US01/23892



WO/02/11112

9/19


PCT/US01/23892



WD 02/11112

10/19


PCT/US01/23892



WO 02/11112

11119


PCT/US01/23892




WO 02/11112

17/19

PCT/US01/23892





WO 02/11112

14/19

PCF/US01/23892





FIG. 15

WO 02/11112

15/19


PCT/US01/23891



WO/02/01112

16/19

PCT/US01/23892



WO 02/11112

17/19

PC/EUS01/23892





FIG. 18



WO 02/11112

19/19

PCT/US01/23892

